


# Product sheet

## IGLAND 350



### Standard equipment

Crane with rotator and grapple. Bogie with 11,5/80 x 15,3/14ply wheels, 2 bolsters, one fixed and one adjustable. The crane is detachable for 3-point linkage tractor mounting. Fold-down stabilizer legs. Without brakes and bogie steering.



### Technical specifications

Length / width	5.4 / 1.9 m
Hydraulic pressure max / min	210 / 160 bar
Tyre dimensions (option)	4x11,5 x 15,3 -14 ply
Max swivel angle	50°
Swivel Force @ 210 Bar	ca. 3.0 tm
Weight	970 kg
Load capacity (n/i loader)	7000 kg
Total weight	8000 kg
Brakes	option
Ground clearance	52 cm
Number of log retaining posts	2 pair
Hydraulic drive power 1.6 t / 175 bar	-
Loaders to fit IGLAND 350	26-47; 32-51; 32-63S

### Optional equipment

Bogie steering with 2 cylinders  
Disc brakes on 2 wheels  
Igland 1601 hydr. Rodio remote controlled winch  
Own Oil Supply, by 540 RPM – 55 l./190 bar, Oil and tubes included  
Extra bolster, compl., adjustable  
Post extension 30 cm  
Tail light board, with 10 m. cable, external  
Tyre chains 2 pcs. (for 11,5/60.15,3)SMT



This model conforms to EU Machine Directive (CE label).

We reserve the right to make changes.

[Printable version](#)



---

**Laeveld Trekkers**

Phone +27 13 758 1233

Fax +27 13 758 1233

Internet: [www.lvt.co.za](http://www.lvt.co.za)

E-mail: [rockydrift@lvt.co.za](mailto:rockydrift@lvt.co.za)

