


Product sheet

IGLAND 380



Standard equipment

Crane with rotator and grapple. Bogie with 4x400/60-15,5/14ply wheels, 2 bolsters, one fixed and one adjustable. The crane is detachable for 3-point linkage tractor mounting. Fold-down stabilizer legs. Bogie steering with 2 cylinders. Without brakes.




Technical specifications

Length / width	5.4 / 2.2 m
Hydraulic pressure max / min	210 / 160 bar
Tyre dimensions (option)	400 - 15.5", 14
Max swivel angle	50°
Swivel Force @ 210 Bar	ca 4.0 tm
Weight	1545 kg
Load capacity (n/i loader)	8500 kg
Total weight	10000 kg
Brakes	disc brakes
Ground clearance	52 cm
Number of log retaining posts	2 pairs
Hydraulic drive power 1.6 t / 175 bar	option
Loaders to fit IGLAND 380	26-47; 32-51; 32-63S

Optional equipment

Disc brakes on 2 wheels
Iglan 1601 hydr. Rodio remote controlled winch
Own Oil Supply, by 540 RPM – 55 l./190 bar, Oil and tubes included
Extra bolster, compl., adjustable
Post extension 30 cm
Tail light board, with 10 m. cable, external
Tyre chains 2 pcs. (for 400/60-15,5) SMT

 This model conforms to EU Machine Directive (CE label).

We reserve the right to make changes.

[Printable version](#)



Laeveld Trekkers

Phone +27 13 758 1233

Fax +27 13 758 1233

Internet: www.lvt.co.za

E-mail: rockydrift@lvt.co.za

